GAINWARD

GAINWARD GeForce RTX 2080 SUPER Phantom

Specifications Process Technology 12nm **Boost Clock** 1815 MHz **CUDA Cores** 3072 Max. TGP 250W Memory Amount 8 GB Memory Clock 7750 MHz Memory Type 256b GDDR6 Memory Bandwidth 496 (GB/Sec)

Key Features

- NVIDIA Turing Architecture, 12nm IC Process
- 16Gbps GDDR6 Memory
- 63T RTX-OPS
- Real-Time Ray Tracing
- Tensor Cores
- NVIDIA® GeForce Experience™
- NVIDIA Ansel
- NVIDIA Highlights
- NVIDIA G-SYNC®-Compatible
- Game Ready Drivers
- Microsoft® DirectX® 12 API, Vulkan API, OpenGL 4/5
- NVIDIA GPU Boost™
- NVIDIA NVLink™ (NVIDIA SLI®)
- VR Ready
- 3* DisplayPort 1.4, HDMI 2.0b and USB Type-C
- HDCP 2.2
- Maximum Total Board Power Include USB-C 285W







Output Support



HDMI: (max. resolution) 4096x2160@60Hz DP *3: (max. resolution) 7680x4320@60Hz USB-C (VirtualLink)

Dimension

Board: 292mm(L)x130mm(W) Cooler: 2.7 slot

Bracket: 2 slot

Accessory

- Manual
- Power cable



GAINWARD Unique Features

Expertool //



- ✓ GAINWARD's Expertool II the brand-new utility adds flexible fan curve control and BIOS saving feature for powerful
- GeForce RTX 2080 SUPER card.



✓ GAINWARD superior hardware design provides massive capability for over-clocking and stable operating environment under all kinds of gaming application.

Minimum System Requirements

HDMI"HDCP

Graphics card require:

- PCI Express-compliant motherboard with one dualwidth x16 graphics slot
- Two 8-pin PCI Express supplementary power connectors
- Minimum 650W or greater system power supply
- Microsoft® Windows® 10 64-bit (November 2018 or later), Windows ®7 64-bit, Linux 64-bit

GW GeForce RTX 2080s Phantom_bar code: 471056224-0962

GAINWARD PHRATOM





GAINWARD superior hardware design

GAINWARD re-designs the entire hardware, that brings higher stability under high current operation (heavy loading operation).

DrMOS

DrMOS is designed to handle high current with low noise operation and less heat generating.





Extreme silent acoustics in heavy loading mode

GAINWARD GeForce RTX 2080 SUPER Phantom runs very quiet under full load operation thanks to the new Phantom fan design.

Extreme cool temperature in heavy loading mode

GAINWARD GeForce RTX 2080 SUPER Phantom performs extremely low GPU temperature even under heavy loading condition.



Dual BIOS (1: Normal, 2: Zero RPM)

GAINWARD provides two VBIOS for GeForce RTX 2080 SUPER Phantom board. Standard VBIOS is set on position #1 of the "dual BIOS switch".

Users can switch to second VBIOS on position #2, adding "Zero RPM" fan control feature to enjoy the quietest experience as well as low GPU temperature.

6-Poles Fan Motor

6-poles fan motor vs 4-poles motor (normal fan)

- Smaller hub size that increases 10% efficiency area of the fan
- Lower power consumption up to 30% current reduce
- Smoother spinning lower electric noise, lower vibration (longer lifespan)

Expertool //

GAINWARD's Expertool *II* – the brand-new utility adds flexible and individual fan curve control and VBIOS saving feature for powerful GeForce RTX 2080 SUPER card.